

32", 36", 48", 52" VENOM



WORLDLAWN®

- Approx. 8 ga. steel floating deck
- Powered by Kawasaki FX730V or FS600V engines
- Dual pumps and wheel motors on 48" and 52"
- Remote Discharge Control (RDC) is an option on 32" and 36" models
- Fold up operator platform to convert to walk behind and allow more units on trailers
- Height adjustment knob for a precise cut on 32" and 36" models
- Walk or ride



EXCEPTIONAL VALUE, WORLD PROVEN PERFORMANCE

32", 36", 48", 52" VENOM / SPEC SHEET

VENOM

STANDARD

Construction:	Approx. 8 ga. steel
Starter:	Electric
Deck Lift:	Hand controlled
Blade Speed:	18,500 FPM
Spindles:	Cast aluminum, maintenance free
Steering:	ZTR hand levers
PTO:	Warner Electric clutch

MODELS

MODEL:	WYS32FS600VL	WYS36FS600VL	MODEL:	WYS48FX730VL	WYS52FX730VL
Cut Width:	32"	36"	Cut Width:	48"	52"
Engine:	Kawasaki FS600V w/ lift	Kawasaki FS600V w/ lift	Engine:	Kawasaki FX730V w/ lift	Kawasaki FX730V w/ lift
Horsepower:	18 (Per SAE: J1995)	18 (Per SAE: J1995)	Horsepower:	23.5 (Per SAE: J1995)	23.5 (Per SAE: J1995)
Transmissions:	Parker HTE	Parker HTE	Transmissions:	Hydro-Gear pumps w/cooling fans	Hydro-Gear pumps w/cooling fans
Fuel Capacity:	4.5 gallons	4.5 gallons	Wheel Motors:	Parker Torqmotors	Parker Torqmotors
Cutting Heights:	1.5"-4.5" 1	.5"-4.5"	Fuel Capacity:	5 gallons	5 gallons
Forward Speed:	0-8 MPH	0-8 MPH	Cutting Heights:	2"-4.5" (6 positions)	2"-4.5" (6 positions)
Reverse Speed:	0-4 MPH	0-4 MPH	Forward Speed:	0-8.5 MPH	0-8.5 MPH
Width:	45" 37.4" w/deflector up	48" 40" w/deflector up	Reverse Speed:	0-4.5 MPH	0-4.5 MPH
Length:	67.5"	67.5"	Width:	59" 48" w/deflector up	65" 53" w/deflector up
Blades:	16" x 2	18" x 2	Length:	72"	72"
Tires-Front:	11-4.00 x 5 smooth	11-4.00 x 5 smooth	Blades:	16.25" x 3	18" x 3
Tires-Rear:	18-7.50 x 10 turf 1	8-8.50 x 10 turf	Tires-Front:	11-4.00 x 5 smooth	11-6.00 x 5 smooth
Weight:	690 lbs	700 lbs	Tires-Rear:	18-10.50 x 10 turf	18-10.50 x 10 turf
			Weight:	740 lbs	750 lbs