

46", 50", 60" VIPER



WORLDLAWN®

- Fabricated steel deck with front reinforcement
- Hydro-Gear EZT transmission on 46" mower
- Hydro-Gear ZT 2800 transmissions on 50" and 60" mower
- Discharge, mulch, or collect
- 3 year residential warranty



EXCEPTIONAL VALUE, WORLD PROVEN PERFORMANCE

46", 50", 60" VIPER / SPEC SHEET

VIPER

MODELS

MODEL:	WYRZ46XS20BS	WYRZ46XS22KW
Cut Width:	46"	46"
Engine:	Briggs & Stratton 40 V-Twin Vertical	Kawasaki FR651V
Horsepower:	20	21.5
Transmissions:	Hydro-Gear EZT	Hydro-Gear EZT

STANDARD

Construction:	11 ga. steel
Final Drive:	Integrated
PTO:	Warner Electric clutch
Fuel Capacity:	4 gallons
Cutting Heights:	1.5"-4.5" (7 positions)
Forward Speed:	0-7 MPH
Reverse Speed:	0-3.4 MPH
Tires-Front:	11-4.00 x 5 smooth
Tires-Rear:	18-9.50 x 8 turf
Blades:	16" x 3
Length:	71.7"
Width:	55"
	47.5" w/deflector up
Wheel Base:	44"
Wheel Track:	30" front 33.8" rear
Weight:	544 lbs

VIPER XL

MODELS

MODEL:	WYRZ50XL26BS	WYRZ50XL24KW
Cut Width:	50"	50"
Engine:	Briggs & Stratton ELS	Kawasaki FR691V
Horsepower:	26	23
Blades:	17.3" x 3	17.3" x 3
Length:	72"	72"
Width:	59"	59"
	51" w/deflector up	51" w/deflector up
Weight:	590 lbs	590 lbs

MODEL:	WYRZ60XL24KW	WYRZ60XL26BS
Cut Width:	60"	60"
Engine:	Kawasaki FR691V	Briggs & Stratton ELS
Horsepower:	23	26
Blades:	20.5" x 3	20.5" x 3
Length:	72"	72"
Width:	68.5"	68.5"
	w/deflector up	61" w/deflector up
Weight:	637 lbs	637 lbs

STANDARD

Construction:	11 ga. steel
Final Drive:	Integrated
Transmissions:	Hydro-Gear ZT-2800
PTO:	Warner Electric clutch
Fuel Capacity:	4 gallons
Cutting Heights:	1.5"-4.5" (7 positions)
Forward Speed:	0-7 MPH
Reverse Speed:	0-3.4 MPH
Tires-Front:	13-5.00 x 6 smooth
Tires-Rear:	20-10.00 x 10 drive
Blades:	16" x 3