# 28", 32" BELT WALK BEHIND



- 2 year commercial or residential warranty
- Ergonomically designed hand grips and controls promote ease-of-use and operator comfort

• Easy pull pin height adjustment on floating deck

 Great for hard-to-reach, narrow spaces

• Discharge, mulch, or collect



## 28", 32" BELT DRIVEN WALK BEHIND / SPEC SHEET

#### STANDARD

Construction:

11 ga. w/front reinforcing bar

Blades:

14.5" x 2

Transmission: 3 speed forward

Final Drive: Belt Clutch: Manual Fuel Capacity: 2 gallons

**Cutting Heights:** 1.5"-4" (4 positions)

Forward Speed: 0-3.55 MPH

Tires-Front: 7 x 2.50-3 smooth

Tires-Rear: 13 x 4.00-6 turf

#### DIMENSIONS

60.5" Length:

38" Width:

30" w/deflector up

Wheel Base: 28.1" Wheel Track-Front: 20.3" Wheel Track-Rear: 22.6"

#### **MODELS**

Intek

Model:

**WY28S11BS Briggs & Stratton**  **WY28S11HD** 

Engine:

Honda GXV340

Horsepower: 10.5\* 10.7\* Starter: Recoil Recoil 324 lbs Weight: 314 lbs

#### **MODELS**

Model:

**WY32S11BS** 

Engine:

**Briggs & Stratton** 

I/C OHV

10.5\* Horsepower: Starter: Recoil Weight: 333 lbs

Model:

**WY32S11BSE** 

Engine:

Weight:

**Briggs & Stratton** 

I/C OHV

Horsepower: 11.5\* Starter: Electric 366 lbs

Model: **WY32S11HD** 

Engine:

Honda

GXV340RT2

Horsepower: 10.7\* Starter: Recoil

Weight: 349 lbs

Model: **WY32S11HDE** 

Engine: Honda

GX390

Horsepower: 11.7\* Starter: Electric

Weight: 433 lbs

#### STANDARD

Construction:

Tires-Front:

11 ga. w/front steel

28"

bar reinforcement

8-3.00 x 4 smooth

Blades: 16.5" x 2

Transmission: 3 speed forward

Final Drive: Belt Clutch: Manual

Fuel Capacity: 2 gallons

**Cutting Heights:** 1.5"-4" (6 positions) Forward Speed: 0-3.55 MPH

Tires-Rear: 13-4.00 x 6 turf

### **DIMENSIONS**

Length: 66.1"

Width: 41.3" 32.8" w/deflector up

Wheel Base: 31.8" Wheel Track-Front: Wheel Track Rear: 23.7"

Per SAE: J1995\*