36", 48" BELT WALK BEHIND



36", 48" BELT DRIVEN WALK BEHIND / SPEC SHEET

STANDARD

Construction: 7 ga. w/front steel

bar reinforcement

18" x 2 Blades:

Transmission: 5 forward & 1 reverse

Final Drive: Belt Clutch: Manual 5 gallons Fuel Capacity:

Cutting Heights: 1.5"-4.5" (7 positions)

Forward Speed: 0-4.7 MPH Reverse Speed: 0-2 MPH

Tires-Front: 9-3.50 x 4 smooth Tires-Rear: 13-6.50 x 6 turf

DIMENSIONS

Lenath: 71.6" 46.9" Width:

39.3" w/deflector up

35.2" Wheel Base: Wheel Track: 29.3" front 28" rear

MODELS

MODEL: **WY3616KW WY3616KWE**

Engine: Kawasaki Kawasaki Model: FS481V FS481V Horsepower: 14.5* 14.5* Starter: Recoil Recoil Weight: 446 lhs 477 lhs

*Per SAE: J1995

DIMENSIONS

36" DECK 48" DECK

Width: 58.5" Width: 46" 49" w/deflector up

42.4" w/deflector up

Lenath: 49" Length: 36"

36", **48**" **FIXED DECK**

STANDARD

Kawasaki Engine: FS481V

Construction:

Horsepower: 14.5 (Per SAE: J1995)

Top Plate: Reinforced 7 ga. steel

10 ga. steel

Side Skirt: 7 ga. **Cutting Heights:** 1"-4" in

1/4" increments

PTO: Electric clutch 5 gallons Fuel Capacity:

MODELS

36" MODEL: WYW36FS481V

Blades: 2-18" high lift Blade Speed: 16,960 FPM

Transmission: 5 forward & 1 reverse

0-5 MPH Travel Speed: Front Wheels: 4.10 x 3.50-4 (4 ply) smooth

Drive Wheels: 13 x 6.50-6

(4 ply) turf

453 lbs Weight:

48" MODEL: WYW48FS481V

Blades: 3-16.25" high lift Blade Speed: 15,408 FPM

Transmission: 5 forward & 1 reverse

Travel Speed: 0-5 MPH Front Wheels: 4.10-3.50 x 4

(4 ply) smooth

Drive Wheels: 13-6.50 x 6 (4 ply) turf

512 lbs Weight:

