

36", 48" HYDRO WALK BEHIND



WORLDLAWN®



- Available with fixed or floating decks
- Long life, maintenance free spindles
- Dual pumps and wheel motors
- Side discharge, bag, or mulching capabilities
- Easy to operate controls
- (RDC) Remote Discharge Control*
- Simple track-on-the-go adjustment (tool-less design)



* 36" and 48" floating decks only

EXCEPTIONAL VALUE, WORLD PROVEN PERFORMANCE

36", 48" HYDRO DRIVEN WALK BEHIND / SPEC SHEET

36" HYDRO

STANDARD

Engine: Kawasaki FS481V
Horsepower: 14.5 (Per SAE: J1995)
Construction: 10 ga. steel
Top Plate: Reinforced 7 ga.
Side Skirt: 7 ga.
Blades: 2-18" high lift
Transmission: 2-Hydro-Gear pumps
Travel Speed: 0-6.5 MPH
Wheel motors: Parker Torqmotor
Front Wheels: 4.10-3.50 x 4 (4 ply) smooth
Drive Wheels: 16-6.50 x 8 (4 ply) turf saver
PTO: Electric clutch
Fuel Capacity: 5 gallons

MODELS

**MODEL: WYW36FS481VH
FIXED**

Cutting Heights: 1"-4" in
1/4" increments

Weight: 503 lbs

**MODEL: WYW36FS481VHF
FLOATING**

Cutting Heights: 1.5"-4.5" in
1/2" increments

Weight: 533 lbs

DIMENSIONS

Width: 46", 42.4" w/deflector up

Length: 36.5"

48" HYDRO

STANDARD

Engine: Kawasaki FS481V
Horsepower: 14.5 (Per SAE: J1995)
Construction: 10 ga. steel
Top Plate: Reinforced 7 ga.
Side Skirt: 7 ga.
Transmission: 2-Hydro-Gear pumps
Travel Speed: 0-6.5 MPH
Wheel Motors: Parker Torqmotor
Front Wheels: 4.10-3.50 x 4 (4 ply) smooth
Drive Wheels: 16-6.50 x 8 (4 ply) turf saver
PTO: Electric clutch
Fuel Capacity: 5 gallons

MODELS

**MODEL: WYW48FS481VH
FIXED**

Cutting Heights: 1"-4" in 1/4" increments

Blades: 2-18" high lift

Weight: 562 lbs

**MODEL: WYW48FS481VHF
FLOATING**

Cutting Heights: 1.5"-4.5" in 1/2" increments

Blades: 3-16" high lift

Weight: 592 lbs

DIMENSIONS

Width: 58.5"
48.8" w/deflector up

Length: 49"